
SPD Magnetic System

toroid + coils (ver. TS-1, TS-2)

A.Kovalenko, E.Perepelkin

«TS-1» model geometry

$\frac{1}{2}$ model symmetry

$$B^{(z)}(x, y, 0) = 0.$$


$$J_T = 40 \frac{A}{mm^2},$$

$$J_{B\setminus F}^{(1,2)} = m80 \frac{A}{mm^2},$$


$$S = 200 \times 20 mm^2,$$

$$I_T = J_T \cdot S = 160 kA,$$


$$I_{B\setminus F} = J_{B\setminus F} \cdot S = m320 kA.$$




«TS-1» model geometry




«TS-1» model geometry




«TS-1». Total $|B|$ field. Surface distribution



«TS-1». Total | B | field. RZ- distribution




«TS-1». Total $|B|$ field. RZ- distribution




«TS-1». Vector field distribution

$$\Omega = \left\{ (r, \varphi, z) : \begin{array}{l} 0 \leq r \leq 3000 \\ \varphi = 0 \\ 0 \leq z \leq 3400 \end{array} \right\}$$



«TS-1». Total $|B|$ field distribution ($r = 0$)




«TS-2» model geometry

No symmetry

$$J_T = 40 \frac{A}{mm^2},$$

$$J_{B\setminus F}^{(1,2)} = 80 \frac{A}{mm^2}.$$




«TS-2». Total $|B|$ field. RZ- distribution

$B_{\max} = 1.217 \text{ T}$


$$\Omega = \left\{ (r, \varphi, z) : \begin{array}{l} 0 \leq r \leq 3000 \\ \varphi = 0 \\ 0 \leq z \leq 3400 \end{array} \right\}$$

$B_{\min} = 0 \text{ T}$




«TS-2». Vector field distribution

$$\Omega = \left\{ (r, \varphi, z) : \begin{array}{l} 0 \leq r \leq 3000 \\ \varphi = 0 \\ 0 \leq z \leq 3400 \end{array} \right\}$$



«TS-2». Total $|B|$ field distribution ($r = 0$)



-
- Field distribution is ready for further use for modeling
 - Necessary field amplitude can be normalized for needed value
 - Further optimization of the system version will be performed